

Code: KC-10

RS-485 KEYBOARD CONTROLLER **KC-10**

Net: **108.02 EUR** Gross: **108.02 EUR**

Device enables quick access to the main functions, such as camera zoom and convenient 3D joystick control. Allows to control the most of camera models at direct mode (presets, routes, vectors control, etc.).



SPECIFICATION

Protocols:	Pelco-D, Pelco-P, native
Baud rates:	2400, 4800, 9600, 19200 bps
Cameras numbers (ID):	0 ... 255
Maximal control distance:	1200 m
Number of controlled devices:	max. 255
Communication standard:	RS-485 terminals
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	4 x 20 LCD
Power supply:	12 / 0.03 A (power adapter included)
Operation temp. / Relative humidity:	0 °C ... 50 °C / max. 90 % (non-condensing)
Weight:	0.57 kg
Dimensions:	166 x 135 x 105 mm
Guarantee:	2 years

PRESENTATION

Top view (the cover of control panel is opened):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view (the cover of control panel is closed):



During operation the hand can comfortably rely on the base:



LCD displays all important information:

```
CamID:001 MonID:001
Protocol: Pelco-d
Baudrate: 2400
```

In the kit:



OUR OPINIONS



- Intuitive control and configuration of the keyboard.
- Modern and ergonomic design.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60